



OpenNMS 101

Tarus Balog

tarus@opennms.com

<http://www.opennms.org/Training>

Module 9: Page Sequence Monitor



Page Sequence Monitor (PSM)

- OpenNMS has a range of monitors, from the simple: ICMP and TCP, to the complex, the PSM and Selenium.
- The Page Sequence Monitor allows for in-depth monitoring of websites and applications.
- You modify the default monitor with a “page-sequence” parameter which lists a series of pages that the monitor should access



Exercise #9: OpenNMS PSM

- Create the PSM-based OpenNMS-Login service detector
- Add it to the localhost node
- Note monitoring status
- Add a monitor to the existing Class polling package and insure monitoring is occurring
- Cause an outage
- Restore the outage

Edit Default Foreign Source

Navigate to Configure → Manage Provisioning Requisitions → Edit Default FS

Detector

Name

Class

port

 ×


url

 ×

Add Parameter Save Cancel

Add OpenNMS - Login Service

- Add the new PSM Detector with port and url
- Save the detector
- Save changes to the Default FS
- Rescan localhost



Create a Monitor Service

```
<service name="OpenNMS-Login" interval="30000" user-defined="true" status="on">
    <parameter key="retry" value="1"/>
    <parameter key="timeout" value="5000"/>
    <parameter key="rrd-repository" value="/usr/share/opennms/share/rrd/response"/>
    <parameter key="ds-name" value="opennmslogin"/>
    <parameter key="page-sequence">
        <page-sequence>
            <page path="/opennms/index.jsp" port="8980" successMatch="Password" virtual-host="${nodeLabel}" />
            <page path="/opennms/j_spring_security_check" port="8980" method="POST" virtual-host="${nodeLabel}" >
                <parameter key="j_username" value="admin"/>
                <parameter key="j_password" value="admin"/>
            </page>
            <page path="/opennms/index.jsp" port="8980" successMatch="Log Out" virtual-host="${nodeLabel}" />
            <page path="/opennms/event/index" port="8980"
                  successMatch="Event Queries" virtual-host="${nodeLabel}" />
            <page path="/opennms/j_spring_security_logout" port="8980"
                  successMatch="input_j_username" virtual-host="${nodeLabel}" />
        </page-sequence>
    </parameter>
</service>

<monitor service="OpenNMS-Login" class-name="org.opennms.netmgt.poller.monitors.PageSequenceMonitor"/>
```

Update poller-configuration.xml

- cd /opt/opennms/etc

- **Run**

```
wget -N http://www.opennms.org/Training/Config/Exercise%209/poller-configuration.xml
```

- **Restart OpenNMS**

```
systemctl restart opennms
```

Might Fail on Restart

```
# systemctl restart opennms
```

Recent Events			
284	12/6/16 21:11:41	Normal	The OpenNMS-Login outage on interface 192.168.122.1 has been cleared. Service is restored.
283	12/6/16 21:11:37	Normal	The OpenNMS-Login outage on interface 127.0.0.1 has been cleared. Service is restored.
282	12/6/16 21:11:31	Normal	The OpenNMS-Login outage on interface 10.0.2.15 has been cleared. Service is restored.
265	12/6/16 21:10:57	Minor	OpenNMS-Login outage identified on interface 192.168.122.1 with reason code: Connection refused.
264	12/6/16 21:10:56	Minor	OpenNMS-Login outage identified on interface 127.0.0.1 with reason code: Connection refused.

Test the New Monitor

Change the “admin” password from “admin”

Home

Please enter a new password and confirm

Password

Confirm Password

|

OK Cancel

Note: Be sure to click "Finish" at the bottom of the user page to save changes.

Note Event, Alarm and Notice

287	12/6/16 21:14:43	Minor	OpenNMS-Login outage identified on interface 127.0.0.1 with reason code: Failed to find 'Log Out' in page content at http://127.0.0.1:8980/opennms/index.jsp.					
<input type="checkbox"/>	35	localhost ↗ ↘	2 Dec 6, 2016 9:14:43 PM ↗ ↘ OpenNMS-Login outage identified on interface 127.0.0.1 with reason code: Failed to find 'Log Out' in page content at http://127.0.0.1:8980/opennms/index.jsp.					
<input type="checkbox"/>	18	287 Minor	Dec 6, 2016 9:14:43 PM			localhost ↗ ↘	127.0.0.1 ↗	OpenNMS-Login ↗